

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF MAILING BY "EXPRESS MAIL"

In re Patent Application of:
MARINET

Serial No. Not yet assigned

Filing Date: Herewith

For: PSEUDO-RANDOM NUMBER
GENERATOR

"EXPRESS MAIL" MAILING LABEL NUMBER 9L70d44d684015

DATE OF DEPOSIT March 13, 2001

I HEREBY CERTIFY THAT THIS PAPER OR FEE IS BEING DEPOSITED
WITH THE UNITED STATES POSTAL SERVICE "EXPRESS MAIL POST
OFFICE TO ADDRESSEE" SERVICE UNDER 37 CFR 1.10 ON THE DATE
INDICATED ABOVE AND IS ADDRESSED TO THE COMMISSIONER OF
PATENTS AND TRADEMARKS, WASHINGTON, D.C. 20031

Eric Link

(TYPED OR PRINTED NAME OF PERSON MAILING PAPER OR FEE)

Eric Link

(SIGNATURE OF PERSON MAILING PAPER OR FEE)

PRELIMINARY AMENDMENT

Director, U.S. Patent and Trademark Office
Washington, D.C. 20231

Sir:

Prior to the calculation of fees and examination of
the present application, please enter the amendments and
remarks set out below.

In the Claims:

Please cancel Claims 1 to 10.

Please add new Claims 11 to 44.

11. A pseudo-random number generator comprising:
a first generator for generating a sawtooth waveform
signal having a first frequency;
a second generator for generating a pulse signal
having a second frequency;
a sampling circuit connected to said first and
second generators for sampling the sawtooth waveform signal
using the pulse signal for generating a sample signal of the
sawtooth waveform at the second frequency; and

In re Patent Application of
MARINET
Serial No. Not Yet Assigned
Filed: Herewith

a coding circuit connected to said sampling circuit for generating pseudo-random numbers based on the sample signal.

12. A pseudo-random number generator according to Claim 11, wherein said coding circuit codes an amplitude of the sample signal so that the pseudo-random numbers are generated based on the coded amplitude.

13. A pseudo-random number generator according to Claim 11, wherein the pseudo-random numbers are output in series.

14. A pseudo-random number generator according to Claim 11, wherein the pseudo-random numbers are output in parallel.

15. A pseudo-random number generator according to Claim 12, wherein said coding circuit comprises a comparator for generating a signal representative of a binary value 1 or 0 based upon whether the amplitude of the sample signal is greater than or less than a reference value.

16. A pseudo-random number generator according to Claim 15, wherein the reference value is equal to a median value of the sawtooth waveform signal.

17. A pseudo-random number generator according to Claim 15, wherein the reference value is equal to a mean value of the amplitude of the sample signal.

In re Patent Application of
MARINET
Serial No. **Not Yet Assigned**
Filed: **Herewith**

18. A pseudo-random number generator according to Claim 17, further comprising an RC circuit having an input for receiving the sample signal from said sampling circuit and an output for generating the mean value to said coding circuit.

19. A pseudo-random number generator according to Claim 12, wherein said coding circuit comprises an analog-to-digital converter which supplies a binary code of N digits in parallel, representative of the amplitude of the sample signal.

20. A pseudo-random number generator according to Claim 11, wherein said first generator comprises:
a capacitor;
switching means for switching a current for charging and discharging said capacitor; and
switching control means for controlling the switching of the current to obtain a succession of charge and discharge cycles of said capacitor.

21. A pseudo-random number generator according to Claim 20, wherein said switching control means comprises:
two comparators each comparing a charging voltage of said capacitor to a reference value and generating a signal when the charging voltage reaches the reference value; and
a latch for storing the signal generated successively by each comparator.

22. A pseudo-random number generator according to Claim 20, wherein said switching means comprises:
a current generator for supplying the current;

In re Patent Application of
MARINET
Serial No. **Not Yet Assigned**
Filed: **Herewith**

a plurality of current mirrors for reproducing the current to enable said capacitor to be supplied in both current flow directions; and

a switch controlled by said switching control means for selecting direction of current flow in said capacitor.

23. A pseudo-random number generator according to Claim 11, wherein said second generator comprises a ring oscillator having an odd number of stages.

24. A pseudo-random number generator according to Claim 23, wherein each stage of said second generator comprises:

an inverter circuit comprising a first transistor and a second transistor connected thereto;

a third transistor connected to said first transistor, and a fourth transistor connected to said second transistor;

a fifth transistor configured as a diode for controlling a gate voltage of said third transistor, and a sixth transistor configured as a diode for controlling a gate voltage of said fourth transistor; and

a current generator for supplying a current to said fifth and sixth transistors.

25. A pseudo-random number generator comprising:

a first generator for generating a sawtooth waveform signal having a first frequency;

a second generator for generating a pulse signal having a second frequency;

In re Patent Application of
MARINET
Serial No. **Not Yet Assigned**
Filed: **Herewith**

a sampling circuit connected to said first and second generators for sampling the sawtooth waveform signal using the pulse signal for generating a sample signal of the sawtooth waveform at the second frequency; and

a coding circuit connected to said sampling circuit for coding an amplitude of the sample signal by generating a signal representative of a binary value 1 or 0 based upon whether the amplitude of the sample signal is greater than or less than a reference value, and pseudo-random numbers being generated based on the coded amplitude.

26. A pseudo-random number generator according to Claim 25, wherein the pseudo-random numbers are output in series.

27. A pseudo-random number generator according to Claim 25, wherein the pseudo-random numbers are output in parallel.

28. A pseudo-random number generator according to Claim 25, wherein said coding circuit comprises a comparator.

29. A pseudo-random number generator according to Claim 25, wherein the reference value is equal to a median value of the sawtooth waveform signal.

30. A pseudo-random number generator according to Claim 25, wherein the reference value is equal to a mean value of the amplitude of the sample signal.

In re Patent Application of
MARINET
Serial No. **Not Yet Assigned**
Filed: **Herewith**

31. A pseudo-random number generator according to Claim 25, wherein said coding circuit comprises an analog-to-digital converter which supplies a binary code of N digits in parallel, representative of the amplitude of the sample signal.

32. A pseudo-random number generator according to Claim 25, wherein said first generator comprises:
a capacitor;
a switching circuit for switching a current for charging and discharging said capacitor; and
a switching control circuit for controlling the switching of the current to obtain a succession of charge and discharge cycles of said capacitor.

33. A pseudo-random number generator according to Claim 25, wherein said second generator comprises a ring oscillator having an odd number of stages.

34. A pseudo-random number generator comprising:
a first generator for generating a sawtooth waveform signal having a first frequency, said first generator comprising

a capacitor,
a switching circuit for switching a current for charging and discharging said capacitor, and
a switching control circuit for controlling the switching of the current to obtain a succession of charge and discharge cycles of said capacitor;
a second generator comprising a ring oscillator for generating a pulse signal having a second frequency;

In re Patent Application of
MARINET
Serial No. **Not Yet Assigned**
Filed: **Herewith**

a sampling circuit connected to said first and second generators for sampling the sawtooth waveform signal using the pulse signal for generating a sample signal of the sawtooth waveform at the second frequency; and

a coding circuit connected to said sampling circuit for generating pseudo-random numbers based on the sample signal.

35. A pseudo-random number generator according to Claim 34, wherein said coding circuit codes an amplitude of the sample signal so that the pseudo-random numbers are generated based on the coded amplitude.

36. A pseudo-random number generator according to Claim 35, wherein said coding circuit comprises a comparator for generating a signal representative of a binary value 1 or 0 based upon whether the amplitude of the sample signal is greater than or less than a reference value.

37. A pseudo-random number generator according to Claim 36, wherein the reference value is equal to a median value of the sawtooth waveform signal.

38. A pseudo-random number generator according to Claim 36, wherein the reference value is equal to a mean value of the amplitude of the sample signal.

39. A pseudo-random number generator according to Claim 35, wherein said coding circuit comprises an analog-to-digital converter which supplies a binary code of N digits in

In re Patent Application of
MARINET
Serial No. Not Yet Assigned
Filed: Herewith

parallel, representative of the amplitude of the sample signal.

40. A method for generating pseudo-random numbers comprising:
generating a sawtooth waveform signal having a first frequency;
generating a pulse signal having a second frequency;
sampling the sawtooth waveform signal using the pulse signal for generating a sample signal of the sawtooth waveform at the second frequency; and
coding the sample signal for generating the pseudo-random numbers.

41. A method according to Claim 41, wherein coding comprises coding an amplitude of the sample signal so that the pseudo-random numbers are generated based on the coded amplitude.

42. A method according to Claim 41, wherein coding comprises generating a signal representative of a binary value 1 or 0 based upon whether the amplitude of the sample signal is greater than or less than a reference value.

43. A method according to Claim 42, wherein the reference value is equal to a median value of the sawtooth waveform signal.

44. A method according to Claim 42, wherein the reference value is equal to a mean value of the amplitude of the sample signal.

In re Patent Application of
MARINET
Serial No. Not Yet Assigned
Filed: Herewith

REMARKS

It is believed that all of the claims are patentable over the prior art. For better readability and the Examiner's convenience, the newly submitted claims differ from the translated counterpart claims which are being canceled. The newly submitted claims do not represent changes or amendments that narrow the claim scope for any reason related to the statutory requirements for patentability. Accordingly, after the Examiner completes a thorough examination and finds the claims patentable, a Notice of Allowance is respectfully requested in due course. Should the Examiner determine any minor informalities that need to be addressed, he is encouraged to contact the undersigned attorney at the telephone number below.

Respectfully submitted,



MICHAEL W. TAYLOR
Reg. No. 43,182
Allen, Dyer, Doppelt, Milbrath
& Gilchrist, P.A.
255 S. Orange Avenue, Suite 1401
Post Office Box 3791
Orlando, Florida 32802
407-841-2330
407-841-2343 fax
Attorneys for Applicants